



welldana®



	<b>Welldana Varenummer</b>	<b>34-180628</b>	<b>34-180630</b>	<b>34-180632</b>	<b>34-180640</b>	<b>34-180642</b>
<b>Info</b>	Til pool (m <sup>3</sup> )	30-60	40-75	50-95	65-120	90-160
	Type	Full Inverter				
	Kølemiddel	R32				
	Volt / Hz	230V~ / 50Hz	230V~ / 50Hz	400V/3N~ / 50Hz	400V/3N~ / 50Hz	400V/3N~ / 50Hz
	Funktion	Opvarmning og køling				
	Godkendelse	CE				
<b>Parameter</b>	<b>Ydelse ved luft 15<sup>0</sup> og vand 26<sup>0</sup>. Luftfugtighed 70%</b>					
	Kapacitet opvarmning (KW)	2.3~9.5	2.87~12.5	4.65~16.0	4.57~19.2	5.57~22.7
	Forbrug (kW)	0.32~2.03	0.41~2.55	0.63~2.92	0.80~3.98	0.80~5.04
	COP	7~4	7~4	7.38~5.48	6.96~4.82	6.96~4.50
	Nominal strøm (A)	15.0	15.0	10.0	15.0	15.0
	Max strøm (A)	20.0	20.0	20.0	20.0	20.0
	Laveste driftstemperatur	-15 C	-15 C	-15 C	-15 C	-15 C
	Blæser hastighed (RPM)	400-600	400-600	400-600	400-600	400-700
	Lydeniveau (Sound Pressure) 1m dB(A)	40-48	41-48	44-50	45-52	45-54
	Tilslutning (mm)	50				
	Anbefalet driftsflow (m3/h)	6.5	7	8.9	9.1	9.7
	Max tryktab (max) MMS	5.5	6	6	11	11
<b>Visuelt</b>	Kabinet	Pulverlakeret metalkabinet				
		Black				
	<b>Display</b>					
	Display	Bluetooth display og vandtæt boks				
	Montage					
<b>Tilbehør</b>	<b>Smart Control</b>					
	Wifi Modul & APP	Ja				
	Manual	DK/UK/SE	DK/UK/SE	DK/UK/SE	DK/UK/SE	DK/UK/SE
	Vibrationsdæmpende ben	Ja/gummi	Ja/gummi	Ja/gummi	Ja/gummi	Ja/gummi
	Tilslutning (mm)	Ø 50 mm	Ø 50 mm	Ø 50 mm	Ø 50 mm	Ø 50 mm
	Rubber Ring	Rubber	Rubber	Rubber	Rubber	Rubber
Dræn tilslutning	Gummi	Gummi	Gummi	Gummi	Gummi	